

Fichier entrer.php

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="fr">
<head>
  <title>Livre d'or</title>
  <meta http-equiv="Content-Type" content="text/HTML; charset=iso-8859-1" />
</head>
<body>
  <?php require_once("connect_db.php"); ?>
  <form action="sauver.php" enctype="multipart/form-data" method="get">
    <p>Nom :
    <input type="text" name="nom"></p>
    <p>Commentaire :
    <td><textarea name="texte" rows="7" cols="22"></textarea></p>
    <p><input type="submit" name="submitButtonName" value="Envoyer"></p>
  </form>
</body>
</html>
```

Fichier sauver.php

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="fr">
<head>
  <title>Livre d'or</title>
  <meta http-equiv="Content-Type" content="text/HTML; charset=iso-8859-1" />
</head>
<body>
  <?php require_once("connect_db.php"); ?>
  <?php
  $nom = $_GET['nom'];
  $texte = $_GET['texte'];
  ?>
  <?php echo $nom ?> a écrit "<?php echo $texte?>".
  <?php
  $sql = "INSERT INTO livreor ( id , nom , texte , date )
  VALUES ( ' , '$nom.' , '$texte.' , NOW() ); ";
  echo $sql;
  $resultat = qdb($sql);
  ?>
</body>
</html>
```

Fichier connect_db.php

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="fr">

<head>
  <title>Base</title>
  <meta http-equiv="Content-Type" content="text/html; charset=iso-8859-1" />
</head>

<body>
  <?php
  $dbhost="localhost";
  $dbuser="root";
  $dbpassword="";
  $dbname="base_cswd";

  $dblink=mysql_connect($dbhost,$dbuser,$dbpassword);

  $db_cswd=mysql_select_db($dbname,$dblink);

  function qdb($sql)
  {
    $resultat=mysql_query($sql);
    if (mysql_errno())
    {
      echo "      MySQL error ".mysql_errno()." : ".mysql_error()."\n<br>";
      echo "Requête MySQL : ".$sql."\n<br>";
      die;
    }
    return $resultat;
  }

  ?>
</body>
</html>
```

Fichier livreor.php

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="fr">

<head>
  <title>Livre d'or</title>
  <meta http-equiv="Content-Type" content="text/html; charset=iso-8859-1" />
</head>

<body>
  <?php require_once("connect_db.php"); ?>
  <?php
  //exécuter une requete mysql
  $sql = "SELECT * FROM livreor;";
  $resultat = qdb($sql);

  //connaitre le nombre d'enregistrements
  $nombre_resultats=mysql_num_rows($resultat);

  // parcourir le tableau des enregistrements
  while ($enregistrement= mysql_fetch_array($resultat));
  {
    echo $enregistrement['nom'];
    echo $enregistrement['texte'];
  }

  ?>
</body>
</html>
```